



XVA - Indoor

Scambiatori di Calore Aria/Aria - Air/Air Heat Exchangers - Luft/Luft Wärmetauscher - Intercambiadores de calor Aire/Aire

Caratteristiche Generali

- Installazione interna/esterna
- Pacco di scambio in alluminio brevettato per garantire grande efficienza con dimensioni ridotte
- Resa specifica 16-85 W/k

Common Features

- Indoor/outdoor installation
- Patented heat exchange core made of aluminium, to ensure high efficiency with compact dimensions
- Specific Heat Transmission 16-85 W/K

Allgemeine Merkmale

- Innen- und Außenmontage
- Patentierter Wärmetauscher aus Aluminium, um maximale Effizienz bei kompakten Ausmaßen zu garantieren
- Spezifischer Wärmeaustausch 16-85 W/K

Características Comunes

- Instalación interior/exterior
- Estructura de intercambio en aluminio patentado para garantizar una gran eficiencia con dimensiones reducidas
- Rendimiento específico 16-85 W/k




Certificazioni - Certifications - Zertifizierungen - Certificaciones

- CE
- EAC
- UL Listed (Codice - Code - Artikelnummer - Codigo = EXW--U-----)



OPTIONAL

CODICE	Colore Speciale - Special Colour Sonderfarbe - Color Especial	Carpenteria - Housing - Gehäuse - Carcasa ALSI304
XVA16	OCAXNS06	OCAXI01
XVA35	OCAXNS03	OCAXI02
XVA50	OCAXNS03	OCAXI02
XVA80	OCAXNS01	OCAXI03
XVA90	OCAXNS01	OCAXI03



XVA16

CODICE - CODE - ARTIKELNUMMER - CÒDIGO	M.U.	XVA1600320	XVA16U1303
UL Listed		--	•
Tensione nominale - Rated voltage - Nennspannung - Tensión nominal	V .-	230 . 1	115 . 1
Frequenza nominale - Nominal frequency - Nennfrequenz - Frecuencia nominal	Hz	50/60	60
Resa specifica - Specific heat transmission - Spezifische Leistung - Rendimiento espècifico	W/K	16	16
Corrente Assorbita - Absorbed Current - Stromaufnahme - Cirriente absorbida	A	0,6	0,6
Fusibile T - T Preufse - Absicherung - Fusibile T	A	2	2
Potenza Assorbita dal ventilatore - Absorbed fan Power - Leistungsaufnahme des Lüfter - Potencia absorbida del ventilador	W	64	40
Temp. interne di funzionamento - Internal operating temp. - Interne Betriebstemperatur - Temp. internas de funcionamiento	min/ max °C	-5 / +55	-5 / +55
Limiti Temperatura lato ambiente - Ambient temperature limit - Umgebungstemperatur - Limites temperatura lado ambiente	min/ max °C	-5 / +55	-5 / +55
Grado di protezione circuito interno - Internal circuit protection rating - Schutzgrad interner Kreislauf - Grado de protección del circuito interno	CE IP	54	--
	UL Type	--	12
Pressione sonora esterna - External sound pressure - Externer Schalldruck - Presión sonora externa	dB(A)	58	58
Altezza / Larghezza / Profondità - Height / Width / Depth - Höhe / Breite / Tiefe - Altura / Anchura / Profundidad	mm	410 x 204 x 109	410 x 204 x 109
Installazione - Installation - Installation - Instalación		Internal / External	External
Termostato meccanico - Mechanical Thermostat - Mechanischer Thermostat - Termostato Mecánico		No	No
Peso - Weight - Gewicht - Peso	kg	4,6	4,6

